




# R6 SERIES SINGLE PHASE INVERTER




R6-5K-S3 | R6-6K-S3 | R6-7K-S3  
R6-8K-S3 | R6-9K-S3 | R6-10K-S3

**AFCI** AFCI (Optional)

**16A** String current up to 16A

 Max. Efficiency 98.8%

 Built-in AC & DC SPD

**110%** 110% AC overloading

 24/7 load monitoring (Optional)



MODEL	R6-5K-S3	R6-6K-S3	R6-7K-S3	R6-8K-S3	R6-9K-S3	R6-10K-S3
DC Input						
Max.PV Array Power [Wp]@STC	7500	9000	10500	12000	13500	15000
Max.DC Voltage [V]	600					
MPPT Voltage Range [V]	90 ~ 550					
Rated DC Voltage [V]	360					
Start Voltage [V]	100					
Min.DC Voltage [V]	80					
Max.DC Input Current [A]	16/16/16					
Max.DC Short Circuit Current [A]	19.2/19.2/19.2					
No.of Strings per MPPT	1/1/1					
No.of MPPT	3					
DC Switch	Integrated					
AC Output [On-grid]						
Rated AC Power [W]	4999	6000	7000	8000	9000	10000
Rated Apparent Power[VA]	4999	6000	7000	8000	9000	10000
Max.Apparent Power[VA]	4999	6600	7700	8800	9900	10000
Max.Output Current [A]	21.7	30	35	40	45	45.5
Current Inrush [A]	30					
Max. AC Fault Current [A]	65		100			
Max. AC Over Current Protection [A]	53		76			
Rated AC Voltage/Range [V]	L+N+PE, 220,230,240/180 ~ 280					
Rated Output Frequency/Range [Hz]	50,60/44 ~ 55,54 ~ 65					
Power Factor [cos φ]	0.8 leading ~ 0.8 lagging					
Total Harmonic Distortion [THDi]	<3%					
Efficiency						
Max. Efficiency	98.2%					
Euro Efficiency	97.8%					
Protection						
Internal Overvoltage Protection	Integrated					
DC Insulation Resistance Detection	Integrated					
Grid Monitoring	Integrated					
GFCI Monitoring	Integrated					
DCI Monitoring	Integrated					
AC Short Circuit Current Protection	Integrated					
AC Grounding Detection	Integrated					
DC Surge Protection	Type II					
AC Surge Protection	Type III (type II optional)					
Overheat Protection	Integrated					
Anti-islanding Protection	AFD					
AFCI Protection	Optional					
Interface						
DC Connection	MC4/H4					
AC Connection	Quick Connector					
Display	LED+APP					

MODEL	R6-5K-S3	R6-6K-S3	R6-7K-S3	R6-8K-S3	R6-9K-S3	R6-10K-S3
Communication Port	RS232+RJ45+DRM					
Communication	Wi-Fi/Ethernet/4G/PLC (optional)					
Load Monitoring	Whole day (optional)					
General Parameters						
Topology	Non-isolated					
Consumption at Night [W]	<1					
Consumption at Standby [W]	<8					
Operating Temperature Range	-40°C to +60°C (>45°C derating)					
Cooling Method	Natural Convection					
Ambient Humidity	0% to 100%					
Altitude	4000m (>3000m derating)					
Noise [dBA]	<35					
Ingress Protection	IP65					
Mounting	Wall Mounting					
Dimensions [H*W*D] [mm]	391*532*202					
Weight [kg]	17.3		18			
Warranty [Year]	5 (Standard) /10/15/20 (Optional)					
Applicable Standard	IEC/EN62109-1/2, EN61000-6-1/2/3/4, IEC61683, IEC60068-2, IEC62116, IEC61727, EA/MEA,VDE0126-1-1/A1, CEI 0-21, VDE-AR-N 4105, AS/NZS4777.2, CQC NB/T 32004, G98/G99, NBR 16149, NBR 16150, C10/11,RD1669,UNE206006, UNE206007,EN50438					

Made in china

Manufacturers: SAJ